



9001

BILL HIRSCH ALCOHOL RESISTANT GAS TANK SEALER (RED LABEL)

QUESTIONS AND ANSWERS

WHO IS GAS TANK SEALER USED BY?

PEOPLE WHO RESTORE, REBUILD, OR REPAIR CARS, BOATS OR ANY OTHER TYPE VEHICLE WITH A FUEL TANK; FIRMS WITH FUEL STORAGE TANKS OR PEOPLE WHO HAVE A TANK THAT NEEDS REPAIRING.

WHAT KIND OF PROBLEMS REQUIRE GAS TANK SEALER?

1. TANKS THAT HAVE RUST INSIDE DUE TO YEARS OF NOT BEING USED.
2. TANKS THAT HAVE AN ACCUMULATION OF "GOO" OR SLUDGE INSIDE WHICH MUST BE REMOVED BEFORE COATING WITH SEALER.
3. TANKS THAT MAY HAVE SEAM LEAKS OR PINHOLE LEAKS.
4. TANKS THAT MAY HAVE ANY OR ALL OF THE ABOVE PROBLEMS.

CAN A TANK BE TREATED WITHOUT REMOVING IT FROM THE VEHICLE?

IN MOST CASES, NO! ONCE IN A WHILE, IF A TANK HAS A MINOR PINHOLE LEAK AT THE BOTTOM AND YOU CAN SEE IT FROM THE FILLER HOLE, IT MAY BE ABLE TO BE TREATED WITHOUT REMOVING THE TANK, BUT TO PROPERLY SEAL A TANK, IT MUST BE REMOVED FROM THE VEHICLE.

WHY IS BILL HIRSCH'S GAS TANK SEALER THE BEST ON THE MARKET?

IT IS BETTER BECAUSE IT SEALS HOLES AND SEAMS FAR BETTER THAN ANY OTHER SEALER. IT HAS GREATER STRENGTH AND AT THE SAME TIME HAS THE FLEXIBILITY THAT A PRODUCT OF THIS TYPE IS REQUIRED TO HAVE; SOMETHING OTHER SEALERS DO NOT HAVE. IT IS A NON-POROUS COATING AND IS NOT AFFECTED BY ALCOHOL OR FUEL MOST FUEL ADDITIVES. IT WILL WORK ON ALL TYPES OF TANKS SUCH AS STEEL, ALUMINUM, GALVANIZED, & FIBERGLASS WHEREAS OTHER SEALERS WILL NOT WORK ON SOME OF THESE METALS. IT IS NOT A MOISTURE CURED URETHANE PAINT THAT IS SOLD BY ONE U.S. COMPANY AS A GAS TANK SEALER. THEIR OWN ADVERTISING TELLS YOU THAT IT IS MOISTURE CURED AND THAT ONCE YOU OPEN THE CAN YOU CANNOT RE-USE IT. THIS TYPE OF SEALER, USUALLY A LIGHT GRAY OR SILVER WILL NOT STICK TO THE INTERIOR SURFACE OF MOST TANKS FOR VERY LONG AND GENERALLY 6-12 MONTHS LATER, WILL BREAK AWAY FROM THE INSIDE OF THE TANK AND WILL TURN INTO A FLOATING PLASTIC BAG INSIDE OF THE TANK. THAT TYPE OF ITEM WHILE BEING RESISTANT TO ALCOHOL WAS NEVER INTENDED TO BE A TANK SEALER AND SHOULD NEVER BE USED IN A FUEL TANK.

DOES BILL HIRSCH'S GAS TANK SEALER HAVE "RUST INHIBITORS" THAT SOME OTHERS DO NOT HAVE?

ALL WHITE OR YELLOW SEALERS ON THE MARKET HAVE RUST INHIBITORS IN THEM. ONE PRODUCT SOLD AS A SEALER, WHICH IS A MOISTURE CURED URETHANE, HAS NO RUST INHIBITORS IN IT AT ALL AND YOUR TANK CAN RUST RIGHT UNDER THEIR COATING. THE MANUFACTURER CLAIMS THAT BECAUSE IT SEALS OUT MOISTURE, THAT IT HAS RUST INHIBITORS. THIS IS NOT SO. YOUR TANK CAN RUST UNDERNEATH THAT TYPE OF COATING BECAUSE IT ATTRACTS MOISTURE.

HOW MANY DIFFERENT KINDS OF GAS TANK SEALER ARE THERE?

THERE ARE REALLY ONLY 2 TYPES OTHER THAN BILL HIRSCH'S WHITE ALCOHOL RESISTANT SEALER. (1) A PVC TYPE NON CURING YELLOW SEALER WHICH HAS BEEN IN USE FOR OVER 50 YEARS. IT HAS GREAT SEALING QUALITIES, RUST INHIBITORS, AND REMAINS VERY FLEXIBLE. IT IS AN EXCELLENT SEALER, BUT NOT RECOMMENDED WHERE FUELS CONTAINING ALCOHOL WILL BE USED, AS ALCOHOL WILL DISSOLVE THIS SEALER. (2) A MOISTURE CURED URETHANE SOLD AS A SEALER BUT WHICH IS NOTHING MORE THAN A LIGHT GRAY OR SILVER PAINT. AS DESCRIBED ABOVE, THIS PRODUCT HAS NO RUST INHIBITORS, WILL NOT ADHERE WELL TO SOME TANK INTERIORS AND IS NOT RE-USABLE.

IS BILL HIRSCH'S GAS TANK SEALER "HAZARDOUS"?

ALL CHEMICAL PRODUCTS ARE HAZARDOUS! ALL SHOULD BE USED WITH EXTREME CAUTION. THERE IS NO SUCH THING AS A NON-HAZARDOUS SEALER. THE SUPPLIER OF THE LIGHT GRAY OR SILVER PRODUCT ADVERTISES THAT HIS IS A NON FLAMMABLE PRODUCT, YET ON THE LABEL OF HIS CAN, IT STATES THAT THE PRODUCT IS HIGHLY FLAMMABLE!!!

1009

WHAT TYPE OF PREPARATION IS NEEDED BEFORE USING BILL HIRSCH'S SEALER?

IF TANK HAS SLUDGE, GUM, OR VARNISH, IT SHOULD FIRST BE CLEANED WITH BILL HIRSCH'S MIRACLE=INDUSTRIAL/MARINE CLEANER & DEGREASER. - USE 1 QUART OF HIRSCH CLEANER TO 1 QUART OF WARM WATER, PUT IN TANK FOR 12-24 HOURS FREQUENTLY AGITATING THE TANK. REPEAT PROCESS UNTIL TANK IS CLEAN. RINSE OUT WITH WARM WATER AND LET DRY THOROUGHLY. YOU MAY NOW INSTALL BILL HIRSCH'S SEALER. HOWEVER, IF TANK APPEARS TO STILL HAVE SOME LIGHT SURFACE RUST, APPLY BILL HIRSCH'S GAS TANK ETCH WHICH WILL NOT ONLY REMOVE THE RUST BUT WILL ETCH THE INSIDE OF THE TANK TO GIVE BETTER ADHESION TO THE SEALER. **JUST DRAIN THE ETCH AFTER USE AND LET TANK AIR DRY COMPLETELY BEFORE APPLYING SEALER. DO NOT FLUSH OUT THE TANK AFTER USING THE ETCH.** WHILE BILL HIRSCH'S SEALER WAS DESIGNED TO BE APPLIED RIGHT OVER LIGHT SURFACE RUST, IT IS STILL BETTER TO USE THE ETCH. HOWEVER, TANKS THAT HAVE A HEAVY BUILDUP OF RUST, USUALLY TANKS THAT HAVE NOT BEEN USED FOR YEARS, WHERE CONDENSATION AND WATER HAVE TAKEN THEIR TOLL, SHOULD BE PROFESSIONALLY CLEANED OUT BEFORE APPLYING SEALER. PROFESSIONAL RADIATOR REPAIR SHOPS AND "READY-STRIP" SHOPS CAN PERFORM THIS WORK

IS IT ALWAYS NECESSARY TO SEAL A TANK AFTER IT HAS BEEN CLEANED?

NO. SEALER SHOULD ONLY BE USED AS A LAST RESORT. TANKS THAT ARE RUST AND GUM FREE THAT HAVE NO PINHOLES OR LEAKS DO NOT NEED SEALER. IT IS HIGHLY RECOMMENDED THAT TANKS BE KEPT FULL WITH FUEL AT ALL TIMES, ESPECIALLY DURING STORAGE. THIS PREVENTS CONDENSATION AND FURTHER RUSTING. BUT IF VEHICLES ARE NOT USED FREQUENTLY OR ARE STORED FOR MORE THAN 2-3 MONTHS AT A TIME, THEY SHOULD BE TREATED WITH BILL HIRSCH'S GASOLINE PRESERVATIVE AND STABILIZER. THIS WILL KEEP THE GASOLINE FRESH FOR UP TO THREE YEARS AND WILL ENSURE QUICK TROUBLE FREE STARTING AFTER MONTHS OF NON USE.

CAN BILL HIRSCH'S SEALER BE RE-USED?

YES!! UNLIKE THE POR PRODUCT THAT MUST BE DISCARDED AFTER THE CAN IS OPENED, BILL HIRSCH'S SEALER IS RE-USABLE IF IT IS NOT ALL USED IN ONE APPLICATION. FURTHER IF BILL HIRSCH SEALER THICKENS AFTER A LONG PERIOD OF NON USE, IT CAN BE RE-THINNED WITH METHYL ETHYL KETONE (MEK).

CAN I REMOVE BILL'S HIRSCH' SEALER FROM THE INSIDE OF MY TANK?

YES, WHILE IT IS DIFFICULT, IT CAN BE REMOVED, WHERE OTHER SEALERS CANNOT. PROFESSIONAL RADIATOR REPAIR SHOPS AND "READY-STRIP" SHOPS CAN EASILY DO THIS. YOU CAN ALSO USE PAINT REMOVER AND METHYL ETHYL KETONE (MEK).

CAUTION!

BEFORE INTRODUCING SEALER INTO THE TANK, THE ENTIRE INTERIOR OF THE TANK MUST BE DRY. IF ONLY ONE SMALL AREA OF THE TANK IS NOT DRY OR HAS FOREIGN MATTER THAT MAY KEEP THE SEALER FROM ADHERING, THE SEALER WILL NOT STICK TO THOSE AREAS AND COULD COME LOOSE AND FLOAT AROUND IN YOUR TANK AND EVENTUALLY COME THROUGH THE FUEL PICK UP TUBE AND CLOG THE FUEL PUMP AND CARBURETOR. THE SOLVENT FOR THIS SEALER IS METHYL ETHYL KETONE (MEK). BEFORE INTRODUCING ANY ADDITIVES TO FUEL TANK AFTER SEALER HAS BEEN INSTALLED, BE SURE THAT THE PRODUCT YOU INTRODUCE DOES NOT CONTAIN (MEK). (MEK) CAN SOFTEN AND LOOSEN THE SEALER WHICH IN TURN CAN CLOG YOUR FUEL LINES, CARBURETOR, ETC. AVOID USING "GUMOUT" OR SIMILAR PRODUCTS WHICH HAVE BEEN KNOWN TO USE (MEK).

IF SEALER IS BEING USED IN A DIESEL TANK, THE TANK MUST BE THOROUGHLY BOILED OR CLEANED OUT BEFORE INTRODUCING SEALER. THIS SEALER IS NOT RECOMMENDED FOR USE IN PLASTIC TANKS.

FINAL NOTE!!

OVER 900,000 CANS OF BILL HIRSCH'S SEALER HAVE BEEN SOLD IN OVER 28 COUNTRIES SINCE IT WAS INTRODUCED 32 YEARS AGO. MORE BILL HIRSCH SEALER HAS BEEN SOLD THROUGHOUT THE WORLD THAN ALL OTHER BRANDS COMBINED. IT IS STILL THE LARGEST SELLING SEALER AND IS THE ONLY SEALER USED IN AIRCRAFT. DOESN'T THAT TELL YOU SOMETHING?

FOR BEST RESULTS USE WHEN TEMPERATURE IS 60 F OR HIGHER.

**FOR ADDITIONAL INFORMATION CALL TOLL FREE 1-800 828 2061
FAX 201 642 6161 WWW.HIRSCHAUTO.COM (E-MAIL) HIRSCHAUTO@AOL.COM
BILL HIRSCH AUTOMOTIVE PRODUCTS • 396 LITTLETON AVE., NEWARK, NJ 07103**

DATA-REV.5-5-97